

CHEMICAL PRODUCTS



- 2-26 ELECTRO
- MARINE 6-66
- Long Term Protection Marine
- Adhesive grease
- Cleansing (detergent)
- Deoxidizing for contacts
- Lubricating for contacts
- Copper paste
- Motors start
- Lithium white grease
- Nautical blue grease
- Technical vaseline grease
- Technical vaseline oil
- Gasket 260° C black
- Gasket 343° C red





2-26 ELECTRO

Water repelling - anti - electrical loss - not insulating.
Dampness ejection, eliminate short circuit and current dispersion due electrolyte
It doesn't affect the conductivity of electric contacts, cleans.

Aerosol - 250 ml
Aerosol - 500 ml
Drum - 20 Lt

RE 31025
RE 31026
RE 31028



MARINE 6-66

Specific protection against corrosion and short circuiting. Water-repelling.
It doesn't affect the conductivity of the electric contacts. It unlocks, cleans and lubricates.

Aerosol - 200 ml
Aerosol - 400 ml
Can - 5 Lt
Drum - 20 Lt

RE 31022
RE 31001
RE 31000
RE 31024



LTPM (LONG TERM PROTECTION MARINE)

Uncorrosive protection long-lasting for marine equipment.
It protects against corrosion of the alloy steel and not steel.

Aerosol - 400 ml
Tin - 20 Lt

RE 31030
RE 31032



ADHESIVE GREASE

It sticks. It lubricates. It's powerful waterproof.
It protects against corrosion. It can't be removed by water or steam.

Aerosol - 200 ml
Aerosol - 400 ml

RE 31033
RE 31002



DETERGENT FOR ELECTRONIC INSTRUMENT

Pure solvent and detergent for electronic systems, instruments, etc.
It eliminated dust, oil, condenses and other kind of dirt.

Aerosol - 300 ml

RE 31003



DETERGENT FOR ELECTRONIC

It eliminates dust, oil, condenses, residual of manual contact, invisible circuit contamination,
components with tension contacts and specific low pressure.

Aerosol - 200 ml

RE 31011



PRODUCT FOR REMOVING OXYDATION FROM CONTACTS

It eliminates the carbon deposit.
It deterges. It desulphorates. It reduces the electronic resistance of the transition between contacts.
It reduces the glitter, the craterisation, the electronic resistance and the voltage drops.

Aerosol - 200 ml

RE 31004



LUBRICANT FOR CONTACTS

Lubricant and protection for electric al systems.
No isolation, no short circuit, it cleans and protect against corrosion.
It cleans and lubricates the movable part of cursors, connectors, switches and so on.
It avoids the oxidation and the blockage of clamps, plugs, threaded connections.

Aerosol - 200ml

RE 31005



COPPER PASTE

It doesn't seize up the low and high temperature.
This specific additive prevent the corrosion towards aluminium.
Application: spline, ribbed pique, nut, studs, threading screw cap, flange, so on.

Can 500 - ml

RE 31034



GEL CYANOACRYLATE

Universal cyanoacrylate adhesive
Suitable to glue on vertical surface
It doesn't leak

Bottle 20 g

RE 31035



MEDIUM THREAD BLOCKER

It replaces washers and self-locking nuts
It blocks nuts and bolts
It seals pneumatic or hydraulic joints
It allows the dismantlement with ordinary tools
It doesn't leak

Bottle 10 g
Bottle 50 g
Bottle 250 g

RE 31036
RE 31037
RE 31038



CABLE PULLING LUBRICANT

It helps to slide electric cables through corrugated pipes
It keeps the lubricating effect for the whole time needed to insert cables
It does not oxidise and it does not isolate cable terminals
Removable with water

Bottle 1 l

RE 31039



CLEANING FOAM FOR METAL SURFACES

Water-based cleaner suitable for stainless steel, aluminium, platings, most part of plastics
It covers with a protective, not oily veil
No dilution necessary, not corrosive, cfc free
It cleans stainless steel polished, matt, satin-finished surfaces

Aerosol 500 ml

RE 31040

LABEL UNSTICKER

It melts glue from stickers and labels in 2-3 min
It takes away every adhesive trace from labels
Supplied with 360° sprinkle valve

Aerosol 200 ml

RE 31041



SILICONIC OIL

Water repelling, anti adhesive, lubricating
It protects metals and rubber, electric insulating
Unalterable, inert and eco-friendly
It prevents from metal oxidation

Aerosol 200 ml
Aerosol 400 ml

RE 31042
RE 31043

TEFLON DRY LUBRICANT

Anti seizing up, anti friction, water repelling
It is not affected by moisture and brackish
Not removable with water, it does not stain
Suitable for wooden and plastic materials, metal and rubber
It leaves a colourless, thin, continuous, flexible film
It lubricates loglines, cables, sticks, hinges, runners

Aerosol 400 ml

RE 31044



	<p>MOTOR STARTER It makes the starter of gas or diesel motors very easy. It avoids the battery to heavy loads or to exhaust. It lubricates the cylinder sides, protect from corrosion and avoids the dilution from motor's oil. It stands mechanical wear and tear.</p> <p>Packing - 200 ml</p>	<p>RE 31006</p>
	<p>LITHIUM WHITE GREASE White lubricant with titanium, zinc and lithium base. It comes applied on pivot, bearing, inside and outside board, rudder and so on.</p> <p>Tube - 125 ml Tin - 500 ml Tin - 1000 ml</p>	<p>RE 31018 RE 31019 RE 31020</p>
	<p>UNCORROSIVE LUBRICANT Semisynthetic grease very adhesive and waterproof, it doesn't come removed by the rain and by sweet or sea water jet, or by centrifugal force. Makes tin the threaded closures. It is indicated for long lasting lubrication and protection of all board implement.</p> <p>Tube - 125 ml Tin - 500 ml</p>	<p>RE 31016 RE 31017</p>
	<p>TECHNICAL VASELINE GREASE Protective and colourness lubricant, inert and ecologic. Adherent and persistent for tools and machine tool, transmission, threaded closures. It protects wood making it water resistant. Anti adhesive for gaskets and closures. Removable with off greasing detergent.</p> <p>Tube - 125 ml Tin - 500 ml Tin - 1000 ml Pail - 5000 ml</p>	<p>RE 31007 RE 31013 RE 31014 RE 31015</p>
	<p>VASELINE OIL Lubricant, protective, colourless, inert and ecological. It protect metals from corrosion and facilitates mechanic parts blockage. Makes wood waterproof. Very practical because is spray solution.</p> <p>Aerosol - 200 ml Aerosol - 400 ml</p>	<p>RE 31012 RE 31008</p>
	<p>BLACK 260°C GASKET Black silionic gasket fast sealing. It substitutes the previous gaskets. Resist to chemical alterations and mechanical deformations provoked by thermal cycles with maximum temperature up to 260°. It assures the seal and seals the eventual looses between high pressure mechanical working elements. Excellent water, oils, mineral oils resistant.</p> <p>Packing - 85 g</p>	<p>RE 31009</p>
	<p>343° RED GASKET It substitutes the previous gaskets. It can resist up to 343° C. It seals perfectly different mechanical surfaces exposed to high temperatures. It creates gasket of different shapes, resistant to mechanical or chemical agents, strong and elastic. Excellent water, mineral or synthetic oil resistant.</p> <p>Packing - 85 g</p>	<p>RE 31010</p>